

Technical data	Parking	Parking Pro	Parking Select
Lane width max.	3.5 m	3.5 m	3.5 m
Opening / closing time	1.8 s	1.3 s	1.3 s
Power consumption max.	35 W	95 W	95 W
Duty cycle	100%		
Supply voltage	Wide voltage range 85 - 264 V AC		
Frequency	50 - 60 Hz		
Drive system	MHTM™ MicroDrive		
Housing dimensions (W x D x H)	315 x 360 x 915 mm		
Weight (without boom)	40 kg		
Housing design	Powder-coated aluminium		
Base frame	Powder-coated stainless steel		
Protection class	IP 54		
Compliant with	2004/108/EG, 2006/42/EG, 305/2011, CE, UL 325		
Temperature range	-30 to +55 °C		

Features	Parking	Parking Pro	Parking Select
Standard colour	RAL 2000	3 variants	freely selectable
Special painting	○	○	●
VarioBoom	●	●	●
Extension Set VarioBoom	-	○	○
Control unit	MGC	MGC Pro	MGC Pro
Integrated 2-channel loop detector	●	●	●
Control unit modularly extendable	Radio control and additional loop detector only	●	●
Variable I/O assignment	-	●	●
Number of digital inputs	8	8	8
Number of relay / digital outputs	6/4	6/4	6/4
Closing times selectable	●	●	●
Opening times selectable	-	●	●
Solar / battery option	○	○	○
Extended accessories	-	○	○
Specified number of cycles	10 Mio	10 Mio	10 Mio
Warranty	2 years	2 years	2 years

- Standard
- Optionally available
- Not available for this model